



1.2 米 检 测 报 告

1.2m Test Report

样 品 名 称: 移动电源

Name of Samples: **Power Bank**

申 请 商 名 称: 鑫匯源(香港)電子有限公司

Applicant's name: **CELLULAR ELECTRONIC TECHNOLOGY (HK)CO., LTD**

深圳市北航检测有限公司
Shenzhen Beihang Testing Co., Ltd.

| General information(基本资料) | | | |
|---------------------------------|---|----------------------|-------------|
| 样品名称 Name of samples | 移动电源 Power Bank | 样品外观颜色 Appearance | 黑色 Black |
| 型号/规格 Type/Mode | POL016 3.7V,10000mAh 3.7Wh | 商标 Trade mark | -- |
| 申请商名称 Applicant's name | 鑫匯源(香港)電子有限公司 CELLULAR ELECTRONIC TECHNOLOGY (HK)CO., LTD | | |
| 申请商地址 Applicant's address | 广东省东莞市塘厦镇凤凰岗大道 17 号楼 3 楼 3/F, Building 17, Fenghuang Gang Avenue, Tangxia Town Dongguan City, Guangdong province, China 523727 | | |
| 生产厂 Factory | 鑫匯源(香港)電子有限公司 CELLULAR ELECTRONIC TECHNOLOGY (HK)CO., LTD | | |
| 生产厂地址 Factory's address | 广东省东莞市塘厦镇凤凰岗大道 17 号楼 3 楼 3/F, Building 17, Fenghuang Gang Avenue, Tangxia Town Dongguan City, Guangdong province, China 523727 | | |
| 鉴定依据 Inspection according to | 联合国《关于危险货物运输的建议书规章范本》(22 修订版) 特殊规定 188 条款 UNITED NATIONS "Recommendations on the TRANSPORT OF DANGEROUS GOODS" Model Regulations (22nd Rev. edition) special provisions 188 | | |
| 测试项目 Test item | 1.2 米跌落测试 1.2m Drop test | | |
| 鉴定结论 Certification | 包装符合联合国《关于危险货物运输的建议书规章范本》(22 修订版) 特殊规定 188 条款 1.2 米跌落测试要求。 The package was capable of withstanding 1.2m drop test of UNITED NATIONS "Recommendations on the TRANSPORT OF DANGEROUS GOODS" Model Regulations (22nd Rev. edition) special provisions 188. Date of issue:/ 签发日期: Nov.30, 2023 | | |

Tested by:

主 检:



Reviewed by:

审 核:



Approved by:

批 准:



| Package information (包装信息) | | |
|---|--|---------------|
| 包装件信息 Information for the package | 每包装件毛重 Gross weight per package | Approx.11.9kg |
| | 每包装件电池的净重 Net quantity of Batteries per package | Approx.9.36kg |
| | 每包装件含电池个数 Number of Batteries per package | 40pcs |
| 包装件所含设备信息 Information for equipment in the package | 设备名称 Name of equipment | -- |
| | 型号 Type/Mode | -- |
| | 商标 Trade mark | -- |
| 备注 / Remarks: 防短路及意外启用的内部包装方式是：独立小包装 The manner of inner packaging that can prevent short circuits and accidental operation: Independent packaging. | | |

Photos of packages (包装照片)

Outer package / 外包装



Inner package / 内包装



Photos of Samples (样品照片)

Power Bank /移动电源 (3.7V,10000mAh 37Wh)



| 1.2m Drop test(1.2 米跌落测试) | | | |
|---------------------------|--|----------------|---|
| Test Items 测试项目 | Drop test 跌落测试 | | |
| 1.1 | Test procedure 测试步骤 | | |
| | <p>The package of batteries is dropped from 1.2m in any orientation. The test floor is concrete floor. 电池的包装件以任意方向从 1.2 米跌落至水泥地面。</p> | | |
| | <p>Each package is capable of withstanding a 1.2m drop test in any orientation without damage to cells or batteries contained therein, without shifting of the contents so as to allow battery to battery(or cell to cell) contact and without release of contents. 每个电池的包装件以任意方向从 1.2 米跌落，而没有造成包装件内的电池或电芯的损坏，也没有移动包装件内的电池或电芯使其相互接触以及包装件内的电池或电芯漏出。</p> | | |
| 1.2 | Result 测试结果 | | |
| | <p>No batteries or cells is damaged or connected by neighbor, the batteries or cells should not be released from package. 包装件内的电池或电芯无损坏，无相互接触。包装件内的电池或电芯不能从包装件漏出。</p> | Surface 面跌落 | The package is not cracked, the contents are not damaged and not shifted. 包装未破裂，内装物完好。 |
| | | Arris 棱跌落 | The package is not cracked, the contents are not damaged and not shifted. 包装未破裂，内装物完好。 |
| | | Angle 角跌落 | The package is not cracked, the contents are not damaged and not shifted. 包装未破裂，内装物完好。 |

--End of Test Report--